



ANCAP Application of Star Ratings Protocol.

v1.9

JANUARY 2022



PREFACE

During the test preparation, vehicle manufacturers are encouraged to liaise with ANCAP and to observe the way cars are set up for testing. Where a vehicle manufacturer feels that a particular feature should be altered, they should raise this with the ANCAP assessor present at the test, or in writing to the ANCAP Chief Executive Officer if no assessor is present. ANCAP will consider the matter and at their sole discretion and give direction to the test facility.

Vehicle manufacturers warrant not to, whether directly or indirectly, interfere with testing and are forbidden from making changes to any feature that may influence the test, including but not limited to dummy positioning, vehicle setting, laboratory environment etc.

Illustrations in this protocol are reproduced from Euro NCAP publications, and therefore show Euro NCAP markings on left-hand-drive vehicles. Where relevant, the layouts depicted should be adapted to right-hand-drive application.

VERSION	PUBLISHED	DETAILS
1.5	December 2017	First version of ANCAP protocol.
1.7	January 2020	Update for 2020 implementation.
1.8	September 2021	Update for 2023 Implementation. Retirement of pre-2018 ANCAP protocols including: • ANCAP Ratings Road Map 2011-2017 • ANCAP Application of ANCAP Safety Ratings to Vehicle Model Variants (June 2016) • ANCAP Notes on Assessment Protocol (July 2016) Amendments and new sections: • 1 Introduction – To make it clear that all existing ANCAP ratings will be subject to this protocol from 1 January 2023 • 2 Definitions – Introduce definitions of Make and Model Name • 7 Corporate Twin – Amendments to definition and align extension of star ratings to Corporate Twins to treatment of Variants and Partner Models • Amend Appendix 1 introduction to include Partner Models and Corporate Twins
1.9	January 2022	Introduce expiry of pre-2018 ANCAP Roadmap Ratings with amendments: 3 Validity of Star Ratings – add footnote to link to Appendix 2 (new) Appendix 2 – introduce expiry timings for ANCAP Roadmap Ratings

© COPYRIGHT ANCAP 2021

This work is the intellectual property of ANCAP with certain content reproduced with the permission of Euro NCAP. A licence is granted for this material to be shared for non-commercial, educational purposes, provided this copyright statement appears on the reproduced materials and notice is given that the copying is by permission of ANCAP. To disseminate otherwise or to republish will be considered a breach of intellectual property rights.

DISCLAIMER.

ANCAP has taken all reasonable care to ensure that the information published in this protocol is accurate and reflects the current technical decisions taken by the organisation. In the event this protocol contains an error or inaccuracy, ANCAP reserves the right to make corrections and determine the assessment and subsequent result of the affected requirement(s).

AUSTRALASIAN NEW CAR ASSESSMENT PROGRAMME APPLICATION OF STAR RATINGS PROTOCOL

TABLE OF CONTENTS

1	Intro	oduction	1
2	Defi	initions	1
3	Vali	dity of Star Rating	2
4	Ann	ual and Facelift Reviews	2
5	Teri	mination of Star Rating	3
6	Vari	iants and Partner Models	4
	6.1	Main Assessment	4
	6.2	Application of Star Rating to Other Variants	4
	6.3	Variants Not Covered by the Rating	4
	6.4	Partner Models	4
	6.5	Timing	5
	6.6	Comparison of Data	5
7	Cor	porate Twins	5
8	Pre	sentation on Website	6
Α	PPEN	DIX 1	7
Α	PPEN	DIX 2	16

1 Introduction

This protocol defines the technical aspects concerning the continued validity of an ANCAP star rating, as well as the assessment of model variants, partner models and corporate twins. Manufacturers should also be careful to observe the requirements of ANCAP's "Guidelines for Use of the Star Rating".

From 1 January 2023 all existing ANCAP star ratings will be subject to this Application of Star Ratings Protocol.

2 Definitions

'Make (brand)'; The make of a motor vehicle must be the marque/brand or name by which that range of motor vehicles is popularly known, or the name of the manufacturer.

'Model Name': the name by which the vehicle is advertised or sold.

'Variant': is a version of the originally-tested vehicle which shares

- Make (brand)
- Model Name (additional descriptions such as 'hatch', 'sportswagon' etc are allowed so long as the basic model name is the same)
- All equipment having an influence on safety
- All important structural elements related to safety performance.
 Where these differ (number of side entry doors, for example), additional data is required

and which can be shown not to differ from the originally-tested vehicle in terms of the ANCAP star rating (see 6.2 for a full description).

'Partner': has the same relationship to the originally-tested vehicle as a variant (same brand) but has a different model name. All important structural elements related to safety performance must be the same as the originally-tested vehicle. Where these differ, additional data is required. Safety equipment and its fitment must be the same as the originally-tested vehicle. See 6.4 for a full description.

'Corporate Twins':

- Are identical to each other is all ways except for Make and Model Name, i.e., they are examples of pure 'badge engineering.' Visually they are identical, and it is clear to consumers that they are in effect, the same vehicle.
- May differ with minor styling changes such as front panels, grill and headlights, but are identical in all other regards including fitment of safety equipment.

3 Validity of Star Rating

Once ANCAP has published the base star rating and related information on its website, the vehicle has obtained a valid rating.

By default, the base rating (and optional rating if applicable) remains valid for a maximum period of 6 years following the release of the result. The rating scheme is expected to change so significantly during this period that referring to an older result would mislead consumers.

If during this period the specification of the rated vehicle or safety pack alters, for instance because standard equipment is deleted or made optional, the rating may become invalid earlier. To monitor changes to rated vehicles, ANCAP will apply Annual and Facelift Reviews (see 4).

In some circumstances the star rating may be carried over from the original test model to a facelifted model, another model variant or twin model. Specific conditions apply as laid out in sections 6 and 7 respectively.

4 Annual and Facelift Reviews

- 4.1 All vehicles will be subject to an annual review of their ratings.
- 4.1.1 A vehicle's base rating will be subject to an annual review every 12 months from the time the original rating was released until maximum 6 years thereafter, to establish whether or not the original rating remains valid. The annual review will comprise (for all variants and/or corporate twins covered by the rating):
 - A check that the base safety equipment is unchanged and will continue so for a further 12 months.
 - A check that the fitment of safety equipment met original requirements and is expected to continue to do so for a further 12 months. This check will require information on total sales across the model range and evidence of the number of vehicles to which the safety equipment was fitted as standard equipment.

Note: Information from a third party should be provided to corroborate the sales figures (e.g. for an AEB system, information might be provided by the supplier of the radar or camera system used in that application).

4.1.2 ANCAP will supply a list to the vehicle manufacturer of all current assessments for which annual review forms should be completed, together with the date they are due. The completed form should be submitted to ANCAP approximately three to four weeks before the due date. The completed form will be reviewed by ANCAP and the manufacturer will be contacted if further

¹ Except as varied by Appendix 2.

- information is required.
- 4.1.3 Not returned or not completed forms may lead to discontinuation of the star rating.
- 4.2 Where a vehicle with a valid overall star rating receives a facelift and the manufacturer wishes to carry over the rating from the original test, the following rules apply:
- 4.2.1 The vehicle manufacturer should contact ANCAP approximately four months before the release of the facelifted vehicle.
- 4.2.2 A 'facelift review' will be conducted by ANCAP to establish whether or not the original star rating can be transferred. This will comprise, in addition to those items examined in an annual review (see above):
 - A review of the changes that have been made to the vehicle.
 - A review of in-house test data, where appropriate.
- 4.2.3 Application should be made even for 'facelifts' which have no influence, or a very minor influence, on the safety rating but where the appearance of the car has been altered or where the car is to be marketed as 'new'. It is ANCAP's intention to keep consumers informed of the applicability of the rating and any changes which distinguish the updated vehicle from the original should be reported.
- 4.2.4 It is the responsibility of the vehicle manufacturer to approach ANCAP with information concerning facelift changes. If no information is received from the manufacturer, ANCAP may assume that the facelifted vehicle does not meet the requirements of the original star rating. The original star rating may no longer be valid and the facelifted vehicle may be eligible for assessment.
- 4.3 The continued validity of an optional rating based on a safety pack will be checked according to VSSTR protocol v7.2 or later.
- 4.4 The outcome of annual reviews and facelift reviews will be published on the web page of the vehicle in a simple tabulated format, indicating the date and nature of the review and whether or not the original rating remains valid. Annual reviews will be published approximately every 12 months from the date of the original rating.

5 Termination of Star Rating

- 5.1 The base rating (and optional rating if applicable) expires after 6 years or when the original rating is not considered valid for the vehicle on sale at an Annual Review (e.g. original fitment rates not met in practice) or a Facelift Review.
- In all cases where the rating has been terminated, the website will list the VIN up to which the rating is valid. Vehicles after this VIN will not be covered by the rating and the manufacturer's advertising should make no further reference to the rating. The ratings and related information will remain on the website for

reference (used car market).

5.2.1 Vehicles produced after this VIN are eligible for testing against the latest ANCAP protocols. The manufacturer may be offered the opportunity to sponsor the upgrade of the rating.

6 Variants and Partner Models

ANCAP will provide information to consumers about the variants to which a model's rating applies. It is intended to provide, on the website and in the datasheet, a list of all variants in the model range and to indicate whether or not the published rating can be considered to apply to that variant. To this end, the equipment matrix sent to vehicle manufacturers, before tests begin, contains a section where all variants, including partner models, must be defined.

6.1 Main Assessment

- 6.1.1 ANCAP will test a single variant, as identified using the Vehicle Specification, Selection, Testing and Retesting (VSSTR) protocol. As part of its assessment of the vehicle, ANCAP will ask the manufacturer for data showing the equivalent safety performance of the opposite hand of drive to the one tested (e.g. RHD if LHD tested).
- 6.2 Application of Star Rating to Other Variants
- 6.2.1 Variants will be considered to share the rating of the tested vehicle if the manufacturer can provide data/information to demonstrate to the satisfaction of the lead inspector that all of the requirements set out in Appendix 1 are met
- 6.2.2 In-house data is acceptable to demonstrate compliance with the requirements of Appendix 1, except where official tests are explicitly demanded in that Appendix.
- 6.2.3 ANCAP reserves the right to request additional information to the above.
- 6.3 Variants Not Covered by the Rating
- 6.3.1 Any variants which do not meet the requirements of 6.2 will be considered not to be covered by the star rating and will be marked as such in the website table.
- 6.4 Partner Models
- 6.4.1 Certain variants may be marketed under a different model name to the originally-tested vehicle. Manufacturers may apply for the star rating to be applied to such 'partner models' following the procedures set out in 6.2.1 to 6.2.3.
- 6.4.2 The Manufacturer must inform ANCAP of its intention to apply for a 'partner' rating at the time of application for assessment of the tested model.

- 6.5 Timing
- 6.5.1 Variants
- 6.5.1.1 Manufacturers may apply for the star rating to be applied to other variants in years later than the one in which the rating was originally published. In such cases, no consideration will be given to the requirements in place at the time of the new application, only those which applied at the time of the original rating. Manufacturers should provide data in support of any application as described in 6.2.1.
- 6.5.2 Partner Models
- 6.5.2.1 A partner model may not share the original rating if it is released in a calendar year more than 2 years later than the date stamp of the original assessment. Manufacturers should provide data in support of any application as described in 6.2.1.
- 6.6 Comparison of Data
- 6.6.1 The Manufacturer must explain any differences in test results that do not comply with the requirements for audit testing set out in the Vehicle Specification, Selection, Testing and Retesting (VSSTR) protocol.

7 Corporate Twins

- 7.1 'A vehicle's star rating can be applied to a Corporate Twin if:
- 7.1.1 ANCAP is satisfied that the Corporate Twin is, apart from Make and Model Name, identical to the vehicle tested in all ways related to safety.
- 7.1.2 The twin has the same base safety specification as the vehicle tested, or better.
- 7.1.2.1 The manufacturer may be asked to provide data/information to the satisfaction of the lead inspector that all of the requirements set out in Appendix 1 are met.
- 7.1.2.2 In-house data is acceptable to demonstrate compliance with the requirements of Appendix 1, except where official tests are explicitly demanded.
- 7.2 An equipment matrix should be completed for all brand models to which the rating will be applied.
- 7.2.1 The matrix should be signed by a representative of that brand.
- 7.2.2 The base safety specification and best-selling variant should be identified for each brand.
- 7.2.3 The manufacturer agrees to notify ANCAP of any changes to standard/optional fitment of safety equipment.
- 7.3 Documentation should be submitted to ANCAP which highlights differences, if

any, in

- Manufacturing plants.
- Suppliers of safety equipment.
- Powertrain options.
- 7.4 Where very minor differences exist, the twin with the lowest base safety specification or the poorer performance will be assessed.
- 7.5 All twins should be made available, on request, for strip-down/parts check at time of inspection or before.
- 7.6 Manufacturers must ask for other brand models to be considered as corporate twins at the time the original assessment is to be done. Retrospective application for twins to 'share' the original rating will not be considered.
- 7.7 Data for publication on the corporate twin will be taken from the original model tested. ANCAP will make no distinction between the models
- 7.8 Twins must have the same date stamp on the rating.

8 Presentation on Website

- 8.1 Presentation of results on ANCAP's website is as follows:
- 8.1.1 Variants are included in the same rating as the originally-tested vehicle and are added to the table of model variants for which the rating is valid.
- 8.1.2 Partners are presented as separate models to the originally-tested vehicle, with their own web pages. The results shown in the assessment of the partner will be a combination of those carried over from the originally-tested vehicle and any additional tests done specifically on the partner. Comments will make clear to consumers that the partner is closely related to the originally-assessed vehicle, to explain why the visual media contains images of tests on that vehicle.
- 8.1.3 Corporate twins are presented as separate models to the originally-tested vehicle, with their own web pages. The results shown for twins will be those of the originally-tested vehicle as the worst-case will have been tested where small differences exist (e.g. pedestrian testing, owing to different grilles, headlamps etc). Comments will make clear to consumers that the twin is closely related to the originally-assessed vehicle, to explain why the visual media contains images of tests on that vehicle.

APPENDIX 1

Requirements for transfer of rating to Variants, Partner Models and Corporate Twins.

For light commercial vehicle models where there is an extensive range of variants, ANCAP will negotiate with the vehicle manufacturer on the appropriate additional evidence required to cover the range of variants on a case-by-case basis.

Note: Additional evidence is required for model variants failing to meet the criteria set out in the tables below. Additional evidence is test data produced in accordance with Euro NCAP / ANCAP protocols. In-house data is acceptable, except where official tests are explicitly demanded.

Table 1. ADULT OCCUPANT PROTECTION

Factor	Criterion	
a) Body style (same number of side entry doors)	For assessment, a transverse vertical plane is defined that is 500mm rearward of the upper seat belt anchorage point for the driver seat. Forward of this plane variants must be identical in design and structure for crashworthiness purposes. Drawings showing overlay of structures should be provided. This includes the front seat belt anchorages but not rear seat belt anchorages.	
a) Body style (different number of side entry doors)	Where a variant differs from the tested vehicle in the number of side entry doors (e.g. a 3 door where a 5 door was tested, or vice versa), and its front-end structure is identical for crashworthiness purposes, additional evidence must be provided (side pole and side AE-MDB). For variants (same brand, same model name) in-house data may be provided. For partner models (same brand, different model names), official ANCAP tests must be done.	
	The same rating can be used for the variant or partner in question if the results of the test are comparable, for adult and child dummies, with those of the originally-tested vehicle.	
	If the shape or H point of the rear seats is different from the tested variant, <i>additional evidence</i> may be requested to demonstrate equivalent performance for the full-width test.	

b) Kerb mass	Variation up to ±10% of the mass of the frontal MPDB test vehicle is allowed, provided the car does not receive a modifier for bodyshell instability. Further evidence may be required in cases where the modifier has not been applied but the stability is considered marginal. For variants where the maximum kerb mass (i.e. including all options, safety-related or otherwise) is between 10 and 20 percent more or less than the mass of the frontal MPDB test vehicle, in-house data for the frontal MPDB, side AE-MDB and side pole tests should be provided. Where the maximum kerb mass is greater than 20 percent more or less than the mass of the MPDB test vehicle, the manufacturer must perform additional official frontal MPDB, side MDB and side pole tests at a Euro NCAP/ANCAP laboratory.
c) Engine (displacement, cylinder configuration, aspiration, block size,	For internal combustion (IC) engines, the same block size & configuration is allowed, irrespective of displacement, aspiration and fuel. Extra components within the engine bay such as LPG convertors and turbo-chargers are acceptable provided that footwell and pedal intrusion are well controlled in the tested vehicle (i.e. 4 points scored for driver's feet and there is no footwell rupture).
type of fuel)	Note that a 4 cylinder result cannot be used for a V6 result and a V6 result cannot be used for a V8, and vice versa, without <i>additional evidence</i> (in-house or official ANCAP frontal MPDB test).
	For electric and hybrid vehicles (where an IC variant was originally tested), additional official Euro NCAP/ANCAP tests are needed for frontal MPDB and side pole tests. Additional factors are checked during tests of electric vehicles, such as battery integrity, so results of IC variants cannot be transferred.
d) Transmission (manual or auto, number of gears)	Any transmission is acceptable.
e) Driven wheels (4x4, 4x2, front-wheel drive, rear wheel drive)	Two wheel drive results (either front or rear) are not interchangeable with an all-wheel-drive variant without additional evidence (frontal MPDB test) due to the effect of the rear driveline. Similarly, front-wheel drive results are not interchangeable with rear-wheel-drive results, without additional evidence.

	Driven wheel differences are acceptable for the side impact and pole tests.
f) Ride height (e.g. height of top of wheel arch) and tyre diameter	In general, a difference of +/-50mm from the tested variant is acceptable for both the frontal MPDB test and the side AE-MDB test. However, manufacturers should submit data illustrating where critical structures are positioned relative to the deformable elements in these tests. The lead inspector may require additional evidence. In any case, additional evidence for the AE-MDB test is required where the ride height is more than 50mm lower than the tested variant.
g) Wheelbase	Wheelbase variation up to $\pm 10\%$ is acceptable. Additional evidence (frontal MPDB test) is required for larger variations.
h) Driver location (left- hand-drive, right-hand drive)	Manufacturers will be asked, as part of the routine assessment of the vehicle, to provide evidence to demonstrate equivalence in results between the hand of drive tested and the opposite hand of drive.
i) Occupant restraint systems	Seat design must have similar restraint-related features, such as anti-submarining pans. Upholstery and adjustment features may vary. Where restraint systems differ, <i>additional evidence</i> is required (additional evidence required may vary depending on the extent of differences).
j) Whiplash	Cosmetic changes such as upholstery materials are acceptable. Where a different seat structure or mounting is used or the seat geometry is changed (other than due to easily compressible materials) additional evidence is required (static and dynamic whiplash tests). Control changes (electric/memory vs. manual) are acceptable.
	Additional evidence is required for variants which have structures rearward of the driver seat, to demonstrate that mechanisms designed to control whiplash injuries have sufficient space to operate. For example, a dual cab whiplash rating cannot be applied to a single cab variant without additional evidence (dynamic whiplash tests).

	k)	Th	ird	row	seats
--	----	----	-----	-----	-------

Official ANCAP tests are needed for the following: rear whiplash assessment; CRS installation; SBR. If points are lost relative to the tested variant in any of these assessments, the score of the poorer performing variant will be used for

- Variants (as they share the assessment on the website)
- Partners which share a common assessment on the website.

For partner models which have separate assessments on the website, the appropriate results will be separately shown.

Where the H point of seats in the second row are different from those of the tested variant, the OEM must supply additional data demonstrating equivalent performance in the frontal MPDB test and the side MDB test.

Table 2. CHILD OCCUPANT PROTECTION

Factor	Criterion	
a) Shape of rear bench	Where the rear seats differ from those in the tested variant, in shape, style or H-point, the OEM must provide data on these differences and additional evidence may be requested to demonstrate equivalent performance for child dynamic tests and CRS installation.	
b) Pretensioners and load-limiters	Where the rear restraints differ from those in the tested variant, additional evidence should be submitted to demonstrate equivalent performance for child dynamic tests and CRS installation.	
c) Third row seats	Official ANCAP CRS installation check needed. Results presented as explained in Adult Occupant Protection, item k.	

Table 3. PEDESTRIAN PROTECTION

Factor	Criterion	
a) Head impact zones	Where a grid was submitted for headform testing of the original assessment, a modified grid should be submitted for variants and partner models. ANCAP may require additional testing to verify some grid locations.	
	Where a grid was not originally submitted:	
	i. Where under-bonnet clearances are less than the tested variant and are within 50mm of the bonnet exterior outer surface <i>additional evidence</i> is required (pedestrian headform impact tests).	
	ii. Similarly, additional evidence is required where the stiffness of components within the prescribed adult and child head impact zones (and to a depth of 50mm below the exterior outer surface) is likely to be greater than the tested variant.	
	If the original assessment had active pedestrian protection (a deployable bonnet, for example) official Euro NCAP/ANCAP tests will be needed for any variants that do not have such equipment.	
b) Upper leg impact zones	Where the leading edge of the bonnet is changed in geometry or the stiffness of components within the prescribed zone is likely to be greater than the tested variant then additional evidence (upper legform tests) is required.	
c) Lower leg impact zones	Where the front bumper bar is changed in geometry or the stiffness of components within the prescribed zone is likely to be greater than the tested variant then <i>additional evidence</i> (legform tests) is required	

d) AEB VRU	Where an AEB VRU system was awarded points, other variants must use the same components, human-machine-interface and software as the system tested: To transfer the rating from the tested variant:	
	To transfer the fathing from the tested variant.	
	i. the system must have the same functional components (e.g. LIDAR, radar transmitter & receiver, and mono or stereo cameras), of the same brand, model and series as tested by Euro NCAP/ANCAP	
	ii. AEB software must be the same as that tested by Euro NCAP/ANCAP.	
	iii. all transmitter, receiver and camera locations must be the same as those tested by Euro NCAP/ANCAP.	
	Where these conditions are not met <i>additional evidence</i> (AEB VRU) is required demonstrating that the system has the same or better performance than the system tested by Euro NCAP/ANCAP.	
e) Ride height	The impact points for pedestrian protection tests depend on the ride height of the vehicle. Where the ride height varies from the tested variant by more than +/-50mm additional evidence is required (all pedestrian tests).	

Table 4. SAFETY ASSIST

Factor	Criterion	
a) Speed Assistance Systems	Where any of the following functions were awarded points, other variants must use the same components, human-machine-interface and software as the system tested by Euro NCAP:	
	i. Camera-based speed limit information function (SLIF)	
	ii. Digital map-based speed limit information function (SLIF)	
	iii. Combined camera and digital map systems	
	iv. Manual speed assistance (MSA) speed warning function	
	v. Manual speed assistance (MSA) speed limitation function	
	vi. Intelligent speed assistance (ISA)	
	Where these conditions are not met additional evidence (speed assist) is required.	
b) AEB Car-to-Car	Where an AEB system was awarded points, other variants must use the same components, human-machine-interface and software as the system tested by Euro NCAP:	
	To transfer the rating from the tested variant:	
	 i. functional components (e.g. LIDAR, radar transmitter & receiver, and mono or stereo cameras) must be the same brand, model and series as tested by Euro NCAP/ANCAP 	
	ii. AEB software must be the same or a later version than that tested by Euro NCAP/ANCAP.	
	iii. all transmitter, receiver and camera locations must be the same as those tested by	

	Euro NCAP/ANCAP.	
Where these conditions are not met additional evidence (AEB Inter-Urban) is required demonstrated that the system has the same or better performance than the system tested by Euro NCAP/ANC		
c) Lane Support Systems	Where a LSS system was awarded points, other variants must be equipped with a system of the same type (LDW/LKA) that uses the same components, human-machine-interface and software as the system awarded points by ANCAP.	
	Where these conditions are not met additional evidence (LSS) is required.	

APPENDIX 2

From December 2022 all ANCAP Pathway ratings and ANCAP Roadmap ratings, issued prior to introduction of the ANCAP Application of Star Rating Protocol in 2018, will expire according to the schedule provided in Table 2.1- Expiry of ANCAP Pathway and Roadmap Ratings.

Table 2.1- Expiry of ANCAP Pathway and Roadmap Ratings

ANCAP 'Assessment Year'	Expiry Timing	Eligible for Reassessment ¹
2015 or earlier	Dec 2022	Jan 2025
2016	Dec 2023	Jan 2026
2017	Dec 2024	Jan 2027

ANCAP Website & Technical Reports

Vehicle models with a ANCAP Pathway or Roadmap rating that is no longer valid will have an "end date" of Dec 20XX added to the vehicle "Year Range" on the ANCAP website and corresponding technical report. For example, Mar 2016 – Dec 2020.^{2,3}

Information for all vehicle models rated by ANCAP (whether current or no longer valid) will continue to be available on the ANCAP website.

Notes:

- ¹ The "Eligible for Reassessment" time will only remain valid if during this period the safety specification of the rated vehicle is not altered prior to this date.
- ² Date is "Build Date" of vehicle as defined in the Road Vehicle Standards legislation and submitted to the Register of Approved Vehicles (Month and Year that the vehicle was substantially completed).

Examples

Example 1: A vehicle model with an ANCAP Pathway rating with a datestamp of 2016 will remain valid up to the end of 2023. An "end date" of Dec 2023 will be added to the ANCAP rating on the ANCAP website and technical report. From the beginning of 2024, the vehicle model (if still available for sale as a new vehicle) will be 'unrated'.

Example 2: A vehicle model with an ANCAP Pathway rating with a datestamp of 2015 will remain valid up to the end of 2022. An "end date" of Dec 2022 will be added to the ANCAP rating on the ANCAP website and technical report. From the beginning of 2023, the vehicle model (if still available for sale as a new vehicle) will be 'unrated'.

³ Unless advised by the vehicle brand of earlier "end date."

Example 3: A vehicle model with an ANCAP Roadmap rating with a datestamp of 2014 (or earlier) will remain valid up to the end of 2022. An "end date" of Dec 2022 will be added to the ANCAP rating on the ANCAP website and technical report. From the beginning of 2023, the vehicle model (if still available for sale as a new vehicle) will be 'unrated'.